



S-Series Specifications



S200



S300

Electrical

Steam

Brew

	Voltage, Single Phase	Amps, Max Draw	Cord Plug Rating, Amps (UL)	Watts per Element	Total Wattage	Tank Capacity, Liters	Watts per Element	Total Wattage	Tank Capacity, Liters
2-Group	220	28	30	2000 x 2	4000	7.7	700 x 2	1400	1.9 x 2
3-Group	220	36	50	2500 x 2	5000	12.3	700 x 3	2100	1.9 x 3

Machine Dimensions

Plumbing

	Height	Width (Inch / mm)	Depth	Machine Weight (Lbs / Kgs)	Shipping Weight (Lbs / Kgs)	Shipping Dimensions L x W x H (Inch / mm)	Direct Connection (Compression)
2-Group	16.9 / 428	27.6 / 702	24 / 610	152 / 69	247 / 112	33 x 36 x 30 / 838 x 914 x 762	3/8" OD
3-Group	16.9 / 428	37 / 940	24 / 610	225 / 102	320 / 145	33 x 46 x 30 / 838 x 1168 x 762	3/8" OD

- Certified by Intertek (ETL) for Sanitation to NSF / ANSI 4
- Certified by Intertek (ETL) for Electrical Safety to ANSI / UL 197
- Certified by Intertek (ETL) for Electrical Safety to CSA C22.2 No. 109
- Certified by KTC for Korean KC Mark
- Certified to IECEE CB Scheme
- CE Compliant (By request)
- C-Tick Compliant (By request)
- Sabre Compliant (By request)

